



**H200014-XX-XX**  
 SERIES NO: \_\_\_\_\_  
 PLATING:  
 0T-Tin-plated  
 G0-G/F 0.8U”  
 PIN Q'PY: \_\_\_\_\_  
 10~40

- Features:
1. 10~40 circuits available;
  2. Material: PA46 UL94V-0;
  3. Contact: Brass;
  4. Finished: Tin-plated;
  5. Mates with H200012-XX housing;

Specification:  
 Current rating: 2A AC/DC  
 Voltage rating: 125V AC/DC  
 Contact resistance: 20mΩ Max.  
 Insulation resistance: 1000MΩ Min.  
 Withstanding voltage: 800VAC/minute.  
 Ambient temperature range: -40°C~105°C.

Dimensional Information (mm)

Circuits	DIM A	DIM B	DIM C	DIM D
10	12.00	8.00	10.70	7.30
12	14.00	10.00	12.70	9.20
14	16.00	12.00	14.70	9.20
16	18.00	14.00	16.70	9.20
18	20.00	16.00	18.70	9.20
20	22.00	18.00	20.70	9.20
22	24.00	20.00	22.70	9.20
24	26.00	22.00	24.70	9.20
26	28.00	24.00	26.70	9.20
28	30.00	26.00	28.70	9.20
30	32.00	28.00	30.70	9.20
32	34.00	30.00	32.70	9.20
34	36.00	32.00	34.70	9.20
36	38.00	34.00	36.70	9.20
38	40.00	36.00	38.70	9.20
40	42.00	38.00	40.70	9.20

REV	Description	DATE	GENERAL TOLERANCES (unless specified)	UNITS	MM	DATE	2010-03-05
A	新版发行	2010-06-05	X.X±0.4	SCALE	1:1	DRAWING	Liu zhi guo
			X.XX±0.25	REV	A	CHECKED BY	Li peng
			X.XXX±0.15	APPROVAL BY	OYSW	APPROVAL BY	OYSW
<b>东莞市恒创连接器有限公司</b> DONG GUAN SHI HENG CHUANG CONNECTOR COMPANY LIMITED PRODUCT NAME: 2.0 mm right angle header PART NUMBER: H200014-XX-XX							